

POWER SOLID **AC EV CHARGER**

PSACC22KW3PHGBTB

22 KW

Features

- ▶ Mode 3: Stationary AC charging pile
- ▶ A variety of safety protection functions: short circuit, over-current, over-voltage,
- ▶ under-voltage, leakage, lightning protection, over-temperature protection, etc
- ▶ Charging start mode: plug and play, swipe card, APP optional.
- ▶ Swipe cardWIFIBluetoothnetwork port and a variety of communication options



Technical Specifications

Model	PSACC22KW3PHGBTB
Power	22KW
Input/Output	400VAC/400VAC
Input frequency	50/60Hz
Output current	32A
Over temperature protection	$\geq 95^{\circ}\text{C}$
Rated residual operating current	AC30mA+DC6mA
Operating temperature	$-30^{\circ}\text{C} - +50^{\circ}\text{C}$
Storage temperature	$-40^{\circ}\text{C} - +85^{\circ}\text{C}$
Relative humidity	5%~95% No condensation
Life time of connector	≥ 10000 times
Mean time between failure	MTBF $\geq 8796\text{h}$
Start method	Plug and play/RFID card/App
Maximum altitude	2000m
Communication	WIFI/BLE/Ethernet/4G Optional
Connector type	IEC 62196-2 Type 2
Weight	9.8 Kg (with cable)
Wiring method	Enter and out at the bottom
Protection	IP66 & IK10
Host dimension	353*256*113(mm)